



The product can be pigmented.

TECHNICAL DATA 05

GRASSELLO PUNTINATO VERDE/ROSSO

Description of product

Decorative dotted lime putty and selected marble powders (500 microns) to create satin/dotted "Venetian Stucco" effect.

Application Field

Basic coating for decorations with a shiny dotted effect, for interiors.

Product characteristics

GRASSELLO PUNTINATO is a special stucco paste. Its characteristic is a mixture of micro-crushed green or red marbles that, once applied, results granular. Further coats of shiny grassello smoothen and sharpen these dots that remain in surface. The colour shades can be personalized by using the colour scheme of the Tintometric system Luxury&Lime. The tradition of lime, produced with an advance technology, aims Bericalce towards the Environment Care and Green Division market. The natural raw materials, accurately selected, give the GRASSELLO PUNTINATO a very high ecologic value: the dispersion of humidity avoids the growth of moulds and bacteriums, without using chemical additives. Non-flammable and low odour.

Technical data	
Name	Grassello Puntinato
Composition	"Dolomitic" Lime Putty (Grassello) minimum 12 month aged marble powders and additives for less than 4%
Aspect	Highly dense paste
Color	Natural white dotted green or red
Dilution	Ready to use (if needed a dilution in water 0-5%)
Quantity per layer	approx. 1,8 - 2,2 m ² /kg
PH	13
Vapour permeability	SD - 0,04m (DIN 52615)
Water absorption	w - 0,3kg / (m ² h0,5) (EN1062-3:2001)
VOC class	VOC 4 g/l - wall paint and subcategory "L" max.value UE2010 30g/l
Specific weight	1,50 kg/l
Packaging	5 - 22,5 kg buckets
Storage	Keep in dry place with temperture min.5° - 30°C max.
Notice	Protect the surfaces in the first 12 hours from application

GRASSELLO PUNTINATO VERDE/ROSSO

Instructions for use

- Prepare the base with a specific Primer, Isolante Acrilico or levelling base like Micro Primer Veneziano of Bericalce
 - Application with stainless steel trowel
 - Base must be clean and dry, any unsubstantial parts, traces of oil or grease must be removed; plaster any irregularity of the base.
 - The product must be applied in 2 phases: 1 coat of GRASSELLO PUNTINATO and 2 coats of Shiny Grassetto. The dotted Grassetto will be spreaded lightly without smoothing the surface during spreading. When dry, the aspect will appear granular similar to Intonachino. It's important that the product be of the right consistence and the dilution according to temperature and the absorption of the base. Application of the 2 final coats of Shiny Grassetto after 12 hours.
 - Temperature of application: 5° to 35°C
 - All lime-based products have a normal drying time according to the thickness but, the real hardness is obtained through carbonation which occurs on contact with the air
- This process could last many months

Notes

The present technical chart has been written by Bericalce's experts and the indicated technical and scientific information have been tested in our own workshop.

Any responsibility regarding the results are due only to the method and conditions used during application of the product.

These indications are a valid support for testing the quality of the product in each specific case.

Date of issue 28.07.2016

Bericalce ITALIA

Via Odorico da Pordenone, 18

36100 Vicenza - ITALIA

Tel./Fax (+39) 0444 929102

Tel. (+39) 0444 923317

Skype: bericalce

info@bericalce.com

bericalce.com