



Suitable for external uses.



The product can be pigmented.

MARMORINO ANTICO "300" BRECCIA/CORALLO/DORATO/SPACE

ANTIQUÉ MARMORINO "300" BRECCIA/CORAL/GOLD/SPACE

Description of product

"Grassello Paste" with selected coloured marble powders (300microns), sands and glimmer for a prestigious satin and semi-shiny Antique Venetian Marmorino finishing effect - medium/fine thickness.

Application Field

Prestigious decorations, medium/fine thickness, satin/semi-shiny finishing for interiors.

Product characteristics

MARMORINO ANTICO "300" is available in the versions: BRECCIA - beige colour, mixed with river sand; CORALLO - pink colour mixed with rose marble; DORATO straw-coloured mixed with yellow marble; SPACE - white, mixed with a special micaceous cork-colour elements. The colour shades can be personalized by using the colour scheme of the Tintometric system Luxur&Lime. The accurate mixture of selected micro-marble produces a stucco in paste, ready to use, which permits a vast range of application methods able to satisfy the most sophisticated decorating requests. The tradition of lime, produced with an advance technology, aims Bericalce towards the Environment Care and Green Division market. The natural raw materials, accurately selected, gives MARMORINO ANTICO "300" a very high ecologic value: the dispersion of humidity avoids the growth of moulds and bacteriums, without using chemical additives. Non-flammable and low odour.

Technical data	
Name	Marmorino Antico "300" Breccia/Corallo/Dorato/Space
Composition	"Dolomitic" Lime Putty (Grassello) minimum 12 month aged, marble powders and additives for less than 4%
Aspect	Dense paste
Color	Natural White dotted beige/pink/gold yellow/cork colour
Dilution	Ready to use (if needed a dilution in water 0-5%)
Quantity per layer	approx. 1,8 - 2,2 m ² /kg
PH	13
Vapour permeability	SD - 0,04m (DIN 52615)
Water absorption	w - 0,3kg / (m ² h0,5) (EN1062-3:2001)
VOC class	VOC 5g/l - wall paint and subcategory "L" max.value UE2010 30g/l
Specific weight	1,65 kg/l
Packaging	5 - 25 kg buckets
Storage	Keep in dry place with temperture min.5° - 30°C max.
Notice	Protect the surfaces from rain in the first 24 - 48 hours after application

MARMORINO ANTICO “300” BRECCIA/CORALLO/DORATO/SPACE

Instructions for use

- Prepare the base with a specific Primer, Isolante Acrilico or levelling base like Isolante Ancorante Primer Berico
 - Application with stainless steel trowel
 - Base must be clean and dry, any unsubstantial parts, traces of oil or grease must be removed; plaster any irregularity of the base
 - Application of 2 or more coatings. After spreading, the grade of brightness will be refined with spatola and/or special clothes. We suggest to apply the second layer after 4 hours to permit the first layer to dry correctly
 - It's important that the product be of the correct consistence and dilution according to the temperature and absorption of the surface
 - Temperature of application: 5° to 35°C
 - All lime-based products have a normal drying time according to the thickness but, the real hardness is obtained through carbonation which occurs on contact with the air
- This process could last many months

Notes

The present technical chart has been written by Bericalce's experts and the indicated technical and scientific information have been tested in our own workshop.

Any responsibility regarding the results are due only to the method and conditions used during application of the product.

These indications are a valid support for testing the quality of the product in each specific case.

Date of issue 01.04.2004

BeriCalce ITALIA

Via Odorico da Pordenone, 18

36100 Vicenza - ITALY

Phone (+39) 0444 929102

Fax (+39) 0444 929102

Skype: bericalce

info@bericalce.com

bericalce.com