

TECHNICAL CHART 23

SETA METALLIC



The product can be pigmented.

Description of product

Shot coating with metallic effect, a resin-based paste with metallic pigments, for a traditional decorative finishing and modern touch.

Application Field

Wall decorative for interiors.

Product characteristics

SETA METALLIC is an elegant decorative finish with an exclusive metallic effect that shimmers and glazes, according to the incidence of light. It's a composition of special resins and metallic fillers in aqueous dispersion. This wall finish shows its best character in classical and prestigious settings.

The colour shades can be personalized by using the colour scheme of the tintometric system Luxury&Lime.

Technical data	
Name	Seta Metallic
Composition	Resins in water solution, inorganic and special metallic pigments
Aspect	Liquid
Color	Gold / Silver / Bronz
Dilution	Ready to use (in water according to spreading needs)
Quantity per layer	approx. 7 - 9 m ² /kg
PH	approx. 7
Vapour permeability	SD - 0,25m (DIN 52615)
Fire reaction	Negative if the product is used on non-flammable surfaces
VOC class	VOC 6g/l - wall paint and subcategory "L" max.value UE2010 30g/l
Specific weight	1,2 Kg/lt
Packaging	1 - 5 Lt packages
Storage	Keep in dry place with temperature min.5° to 30°C
Notice	Protect surfaces during the 12 hours after application

SETA METALLIC

Instructions for use

- Application with stainless steel trowel, decorating tools (sponges, pads, gloves, paintbrush)
- Application of 1 or more coats
- Base must be clean and dry, any unsubstantial parts, traces of oil or grease must be removed; plaster any irregularity of the base
- Prepare the base with a specific primer. The product can be applied on Venetian Micro Primer or on paint Decor Fondo of Bericalce
- Application can be done in various ways:
Normally one creates the Venetian Spatolato effect by using the trowel. Otherwise also paintbrush, sponge or decorating gloves can be used alternating in a fancy way the different application phases. According to the dilution of the product and eventual contrasts with mat base, it's possible to obtain particular and new effects
- Temperature of application 5° to 35°C

Notes

The present technical chart has been written by Bericalce's experts and the indicated technical and scientific information have been tested in our own workshop.

Any responsibility regarding the results are due only to the method and conditions used during application of the product.

These indications are a valid support for testing the quality of the product in each specific case.

Date of issue 01.04.2004

Data di revision 1 13.09.2016

Bericalce ITALIA

Via Odorico da Pordenone, 18

36100 Vicenza - ITALIA

Tel./Fax (+39) 0444 929102

Tel. (+39) 0444 923317

Skype: bericalce

info@bericalce.com

bericalce.com