



The product can be pigmented.

TECHNICAL CHART 24

# **MEDITERRANEO**

### **Description of product**

Fine decorative coating composed of minerals and natural fibres to reproduce the antique and rustic plaster, finished with overlapping chromatic colours.

### **Application Field**

Decorative coating for interiors.

### **Product characteristics**

MEDITERRANEO is a decorative finishing composed of minerals and natural fibres which permits to reproduce antique and rustic plasters with overlapping chromatic colours. MEDITERRANEO is a interior coating that can be applied on any kind of surface. The colour shades can be personalized using the colour scheme of the Tintometric system Luxury&Lime.

|                     | Technical data   |
|---------------------|--|
| Name                | Mediterraneo   |
| Composition         | Minerals and natural fibres                                      |
|                     |  |
| Aspect              | Dense paste  |
| Color               | Natural White  |
| Diluition           | Ready to use (eventual dilution in water 0-5%)                   |
| Quantity per layer  | approx. 1 - 2 m2/kg  |
| PH                  | 8,5  |
| Vapour permeability | SD - 0,06m (DIN 52615)   |
| Fire reaction       | w - 0,5kg / (m2h0,5) (EN1062-3:2001)                             |
| VOC class           | VOC 4g/l - wall paint and subcategory "L" max.value UE2010 30g/l |
| Specific weight     | 1,2 kg/l   |
| Packaging           | 25 kg buckets  |
| Storage             | Keep in dry place with temperture min.5° - 30°C max.             |
| Notice              | Protect the surfaces during the 12 hours after application       |

## **MEDITERRANEO**

### Instructions for use

• Prepare the base with a specific Primer, Isolante Acrilico or levelling base like Isolante Ancorante Primer Berico

- Application with stainless steel or plastic trowel
- Application of 1 or more coatings
- Base must be clean and dry, any unsubstantial parts, traces of oil or grease must be removed; plaster any irregularity of the base
- Spread with a plastic trowel a thick coat of MEDITERRANEO, crossing paths as to leave evident traces of the trowel.
- When dry, finish with coloured waxes or veiling
- Temperature of application 5° to 35°C

### Notes

The present technical chart has been written by Bericalce's experts and the indicated technical and scientific information have been tested in our own workshop.

ten by Bericalce's experts and the data given are technical and scientific information tested in our own workshop. Any responsability regarding the results are due only to the method and conditions used during application of the product.

These indications are a valid support for testing the quality of the product in each specific case.

### Date of issue 01.04.2004

#### BeriCalce ITALIA

Via Odorico da Pordenone, 18 36100 Vicenza - ITALY Phone (+39) 0444 929102 Fax (+39) 0444 929102 Skype: bericalce info@bericalce.com



Page 2of2