



## TECHNICAL CHART 26

# SPATOLATO VENEZIANO "HIGH GLOSS"

## Description of product

New concept of synthetic shiny finishing, a very fine mixture of marble powders, alkyd resins, natural oils and essences.

## Application Field

Interior decorative covering.

## Product characteristics

SPATOLATO VENEZIANO "HIGH GLOSS" is a new concept product, which particular mixture makes it easier to work than other similar products, using a simple stainless steel trowel to obtain mirror shiny surfaces. Easy to spread and it needs only two coats to give the desired effect, one as coating and one as polishing are sufficient to obtain its characteristic colour effect. The colour shades can be personalized using the colour scheme of the Tintometric system Luxury&Lime. SPATOLATO VENEZIANO "HIGH GLOSS" is ready to use, but if necessary, dilution with water is possible. It's a product that, thanks to the mixture of natural substances, leaves wall traspiring

Technical data	
Name	Spatolato Veneziano High Gloss
Composition	Natural resins mixed with marble powders and precious oils
Aspect	Dense paste
Color	Natural White
Dilution	Ready to use (eventual dilution in water 0-5%)
Quantity per layer	approx. 4 - 5 m <sup>2</sup> /kg
PH	11
Vapour permeability	SD - 0,04m (DIN 52615)
Water absorption	w - 0,3kg / (m <sup>2</sup> h0,5) (EN1062-3:2001)
VOC class	VOC 3g/l - wall paint and subcategory "L" max.value UE2010 30g/l
Specific weight	1,75 kg/litre
Packaging	10 kg buckets
Storage	Keep in dry place with temperture min.5° - 30°C max.
Notice	Protect the surfaces during the 12 hours after application

# **SPATOLATO VENEZIANO "HIGH GLOSS"**

---

## **Instructions for use**

- Application with stainless steel trowel
- Application of 2 or more coatings
- Ready to use, stir and colour it carefully before use
- Base must be clean and dry, any unsubstantial parts, traces of oil or grease must be removed; plaster any irregularity of the base
- We suggest a specific Primer, Isolante Acrilico or levelling base, like Micro-Primer Veneziano of Bericalce
- Before every further application attend that surface be completely dry
- Grade of brightness will be define with a final step using trowel and/or specific tools
- Reparable: an expert is able to repair the SPATOLATO VENEZIANO "HIGH GLOSS" in case of damage or breakage,
- Temperature of application 5° to 35°C

## **Notes**

The present technical chart has been written by Bericalce's experts and the indicated technical and scientific information have been tested in our own workshop.

Any responsibility regarding the results are due only to the method and conditions used during application of the product.

These indications are a valid support for testing the quality of the product in each specific case.

**Date of issue 01.04.2004**

**Revision nr.1 19.09.2016**

## **Bericalce ITALIA**

Via Odorico da Pordenone, 18

36100 Vicenza - ITALY

Phone (+39) 0444 929102

Fax (+39) 0444 929102

Skype: bericalce

info@bericalce.com

**bericalce.com**