



Suitable for external uses.



The product can be pigmented.

# MICROPRIMER VENEZIANO

## VENETIAN MICROPRIMER

### Description of product

Micro-granular covering anchor primer to be applied with paintbrush or roller. To be used as generic primer for any kind of decoratives even lime-based products (maximum granulometric 100 micron).

### Application Field

Micro-granular primer for interiors and exteriors.

### Product characteristics

MICROPRIMER VENEZIANO is an innovative product, especially studied for surfaces that need a strong anchor primer. Often, the technicians must apply spatolati or marmorini on smooth or treated surfaces: from here the necessity of a product to guarantee a solid and strong anchorage, composed of high adherence vinyl resins mixed with micro-marble grits sifted at 100micron. MICROPRIMER VENEZIANO is dense and once diluted, the thixotropic remains and does not drain; the micro-grits remain homogenously mixed in the paste to obtain an uniform wall application. The final aspect will appear slightly rough and white colour. The colour shades can be personalized using the colour scheme of the Tintometric system Luxury&Lime. Excellent for applications on cement, plaster, bricks, plasterboards and old hydro-paints.

Technical data	
Name	Microprimer Veneziano
Composition	Vinyl resins mixed with powders and micro-marble grits
Aspect	Dense Paste
Color	White
Dilution	In water 10 - 25%
Quantity per layer	approx. 5 - 7 m <sup>2</sup> /kg
PH	9,5
VOC class	VOC 5g/l - wall paint and subcategory "L" max.value UE2010 30g/l
Specific weight	1,58 kg/litre
Packaging	5 - 15 lt packaging
Storage	Keep in dry place with temperture min.5° - 30°C max.
Notice	Protect the surfaces during the 12 hours after application

# MICROPRIMER VENEZIANO

---

## Instructions for use

- Application with paintbrush and roller
- Application of 1 or more coatings
- Base must be clean and dry, any unsubstantial parts, traces of oil or grease must be removed; plaster any irregularity of the base
- In order to keep unvaried the thixotropy of the product and to guarantee adherence, we suggest a dilution of not more than 25%
- On difficult surfaces, we suggest a low dilution
- The product can be applied on many kinds of surfaces (marmorino, grassello, plasterboard, wood panels, etc.) ensuring an excellent adherence and good solid base for further applications
- The product is composed of vinyl resin (30%) with micro-marble grits, therefore does not tarnish if spatolato
- Temperature of application 5° to 35°C

## Notes

The present technical chart has been written by Bericalce's experts and the indicated technical and scientific information have been tested in our own workshop.

Any responsibility regarding the results are due only to the method and conditions used during application of the product.

These indications are a valid support for testing the quality of the product in each specific case.

**Date of issue**            **25.01.2022**

**Date of revision 1**   **28.01.2025**

## **Bericalce S.r.l.**

Via Piave, 23

36033 Isola Vicentina (VI)

Tel. 0039 444 929102

Skype: bericalce

info@bericalce.com

**bericalce.com**