



TECHNICAL CHART 59

DECORATIVE BASECOAT

Description of product

Universal leveling stucco, composed by very fine marble powders, specialty resins, oils and natural essences.

Application Field

Synthetic leveling for interior and exterior, excellent as a base for decorative, for smoothing fine.

Product characteristics

DECORATIVE BASECOAT is a synthetic leveling, leveling, filling, by the excellent thickening power.

Its particular mixture makes it more workable than other similar products.

DECORATIVE BASECOAT is extremely smooth, fine and consistent, and ensures a high degree of spreadability.

The product is ready to use, but if necessary, can be diluted with water. It is a product that provides good breathability where applied to the walls, thanks to its careful composition.

	Technical data
Name	Decorative Basecoat
Composition	Special resin mixed with marble dust and fine oils
Aspect	Dense paste
Color	Natural white
Diluition	Ready to use (0÷5% in water)
Quantity per layer	approx. 5 - 7 m ² /Kg
PH	approx. 7,5-8
Vapour permeability	SD ~ 0,04 m (DIN 52615)
Water absorption	$w \sim 0.3 \text{ Kg (m}^2 \text{ h0,5) (EN 1062-3:2001)}$
VOC class	VOC 30 g/l, wall paint and subcategory "L" max.value UE2010 30g/l
Specific weight	1,775 Kg/lt
Packaging	5 - 25 Kg packages
Storage	Keep in dry place with temperature 5°÷30°C
Notice	Protect surfaces during the 12 hours after application

TECHNICAL CHART 59

DECORATIVE BASECOAT

Instructions for use

- Application with stainless steel trowel.
- The product is ready to use, mix carefully before use.
- Make sure the surface is clean and dry.
- We recommend the bottom leveling type MICRO-PRIMER VENETIAN of Bericalce.
- Temperature of application 5°÷35°C

Notes

The present technical chart has been written by Bericalce's experts and the indicated technical and scientific information have been tested in our own workshop.

Any responsability regarding the results are due only to the method and conditions used during application of the product.

These indications are a valid support for testing the quality of the product in each specific case.

Date of issue 13.09.2016

BeriCalce ITALIA

Via Odorico da Pordenone, 18 36100 Vicenza - ITALIA Tel./Fax (+39) 0444 929102 Tel. (+39) 0444 923317 Skype: bericalce info@bericalce.com

bericalce.com