

TECHNICAL **CHART 60**

METALLIC SANDS



The product can be pigmented.

Description of product

A syntetic decorative, composed by sands and pearlescent fillers, with a metallic effect.

Application Field

Syntetic decorative for interiors, applied on plaster, lime, cement, gypsum and other standard support.

Product characteristics

METALLIC SANDS is a "ready to use" decorative, composed by sands and pearlescent fillers, with a metallic effect. There are no words to describe the beauty and the uniqueness of our "Metallic Sands", since they are absolutely fascinating and unusual due to their intrinsic nature.

In fact, the 11 tints are not obtained through dye mixtures, but through natural colored pearlescent fillers and sands.

This feature gives an incredible and unique nuances to the "Metallic Sands" tints.

The colour shades can be personalized by using the colour scheme of the tintometric system Luxury&Lime.

Technical data	
Name	Metallic Sands
Composition	Resins in water solution, sands and special metallic pigments
Aspect	Liquid
Color	Silver / Gold / Champagne / Amber / Bronze / Brown Topaz / Copper / Green Jasper / Hematite / Intense Gold / Red Cardinal
Dilution	Ready to use (in water according to spreading needs)
Quantity per layer	approx. 8 - 10 m ² /l
PH	approx. 7 - 8
Vapour permeability	SD - 0,25m (DIN 52615)
Fire reaction	Negative if the product is used on non-flammable surfaces
VOC class	VOC 0,5 g/l - wall paint and subcategory "L" max.value UE2010 30g/l
Specific weight	1,25 Kg/l
Packaging	1 - 2,5 - 5 Lt packages
Storage	Keep in dry place with temperature min.5° to 30°C
Notice	Protect surfaces during the 12 hours after application

METALLIC SANDS

Instructions for use

- The product is ready to use. Mix well before use.
- Application of 1 coat.
- Base must be clean and dry, any unsubstantial parts, traces of oil or grease must be removed; plaster any irregularity of the base
- Prepare the base with a specific primer. The product can be applied on MICRO-PRIMER VENEZIANO or on DECORATIVE BASECOAT of Bericalce.
- Apply the product METALLIC SANDS of the chosen color, using a SPATULA or a BRUSH.
- Temperature of application 5° to 35°C

Notes

The present technical chart has been written by Bericalce's experts and the indicated technical and scientific information have been tested in our own workshop.

Any responsibility regarding the results are due only to the method and conditions used during application of the product.

These indications are a valid support for testing the quality of the product in each specific case.

Date of issue 01.08.2016

Bericalce ITALIA

Via Odorico da Pordenone, 18

36100 Vicenza - ITALIA

Tel./Fax (+39) 0444 929102

Tel. (+39) 0444 923317

Skype: bericalce

info@bericalce.com

bericalce.com