



The product can be pigmented.

TECHNICAL **CHART 86**

LAMINA ADHESIVE

Description of product

Concentrated liquid adhesive, in aqueous emulsion, specially formulated for the "Lamina" product.

Application field

Adhesive emulsion that allows the application of "Lamina Foil".

Product characteristics

LAMINA ADHESIVE prepares the treated surfaces forming a film with the following characteristics:

- high adhesiveness;
- excellent resistance to temperatures;
- excellent chemical and mechanical resistance.

Technical data	
Name	Lamina Adhesive
Composition	Blend of synthetic rubbers, resins and cross-linking agents
Aspect	White emulsion
Color	Transparent
Dilution	Ready to use
Quantity per layer	ca. 18 m ² /l
VOC class	VOC 0 g/l, wall paint and subcategory "L" max.value UE2010 30g/l
PH	5
Storage	1 - 5 liters packages
	The product remains unchanged for at least one year if kept in a closed and sheltered environment at a temperature between 5 - 35 °C. Protect from frost!

LAMINA ADHESIVE

Instructions for use

- Application with roller
- The product is applied in 1 or more coats
- Apply the product on completely dry surfaces

Note

The present technical chart has been written by Bericalce's experts and the indicated technical and scientific information have been tested in our own workshop.

Any responsibility regarding the results are due only to the method and conditions used during application of the product.

These indications are a valid support for testing the quality of the product in each specific case.

Date of issue 14.11.2018

BeriCalce ITALIA

Via Odorico da Pordenone, 18

36100 Vicenza - ITALIA

Tel./Fax (+39) 0444 929102

Tel. (+39) 0444 923317

Skype: bericalce

info@bericalce.com

bericalce.com