

TECHNICAL **CHART 88**

LAMINA VARNISH

Description of product

A self cross-linking acrylic varnish for the protection of "Lamina" product, with a high transparency, an excellent resistance and a blocking effect.

Application field

Protective varnish to apply right after the peeling of "Lamina Foil".

Product characteristics

LAMINA VARNISH protects the treated surfaces forming a transparent and strong film, which has the following characteristics:

- high gloss;
- excellent blocking resistance;
- excellent chemical and mechanical resistance.

Technical data	
Name	Lamina Varnish
Composition	Acrylic resin
Aspect	Glossy liquid
Color	Transparent
Dilution	Ready to use
Quantity per layer	approx. 18 m ² /l
VOC class	VOC 0 g/l, wall paint and subcategory "L" max.value UE2010 30g/l
PH	8
Packaging	1 liter packages
Storage	The product remains unchanged for at least six months if kept in a closed and sheltered environment at a temperature between 5 - 35 °C. Protect from frost!

LAMINA VARNISH

Instructions for use

- Application with roller
- The product is applied in 1 or more coats
- Apply the product right after the peeling of "Lamina Foil"

Note

The present technical chart has been written by Bericalce's experts and the indicated technical and scientific information have been tested in our own workshop.

Any responsibility regarding the results are due only to the method and conditions used during application of the product.

These indications are a valid support for testing the quality of the product in each specific case.

Date of issue 14.11.2018

BeriCalce ITALIA

Via Odorico da Pordenone, 18

36100 Vicenza - ITALIA

Tel./Fax (+39) 0444 929102

Tel. (+39) 0444 923317

Skype: bericalce

info@bericalce.com

bericalce.com