



The product can be pigmented.

TECHNICAL CHART 142

CLAY WASH

Description of product

Semi-transparent decorative glaze based on selected natural clays and marble powders, in an aqueous solution, designed to create harmonious finishes for interior decoration.

Application field

Decorative matte-effect veiling finish for interior use (not suitable for application in areas in contact with water).

Product characteristics

CLAY WASH is a breathable matte veiling with a natural character, ideal for creating high-quality decorative effects, such as refined shading with an antique appearance.

Carefully selected raw materials give CLAY WASH a very high ecological value and excellent quality.

The product can be customised using the colourants of the Bericalce tintometric system.

Technical data	
Name	Clay Wash
Composition	Select natural clays, marble powders, binders, in aqueous solution
Aspect	Thick Liquid
Color	White/milky transparent
Dilution	Ready to use (dilution in water up to 50%)
Quantity per layer	ca. 0,05 lt/m ²
PH	11
VOC Class	VOC 0 g/l, wall paints and subcategories "L" EU limit value 2010 30g/l
Specific weight	1,2 Kg/lt
Packaging	5 -1 lt containers
Storage	Store in a dry place with temp. 5° ÷ 30°C. Close well the started packages.
Notice	Protect surfaces in the 24 hours after application.

CLAY WASH

Instructions for use

- Application with brush, sponge.
- Application of 1 or more coats, according to finishing needs.
- Base must be clean and dry; remove any loose or friable parts, as well as traces of oil or grease. Level any surface irregularities beforehand.
- It is recommended to apply CLAY WASH over completely dry decorative finishes.
- CLAY WASH is ready to use, easily tintable, and can be diluted according to specific decorative requirements.
- It is important that the material has the correct consistency and dilution. Consumption and drying times may vary depending on temperature and substrate absorbency.
- Application temperature: 5°C – 30°C.

Notes

As the product is natural, slight color differences between production batches cannot be ruled out.

The suitability of application of the entire stratigraphy, consisting of primer and plaster, should be verified on the basis of a sufficiently large sample.

This data sheet was prepared by Bericalce technicians and the data provided constitute the technical and scientific indications tested at the in-house laboratory.

All responsibility, about the results obtained, lies solely with the method and conditions adopted for the application of the product.

These indications constitute valid support in verifying the suitability of the product for the specific case.

Date of issue **19.07.2024**

Date of revision 2 **06.05.2026**

BeriCalce S.r.l.

Via Piave, 23

36033 Isola Vicentina (VI) - ITALIA

Tel./Fax (+39) 0444 929102

Tel. (+39) 0444 654919

Skype: bericalce

info@bericalce.com

bericalce.com